

Piston and Cylinder Set

Model: 2K S 56 - CP (stock) & 2K 56 - CP (custom)

Stock Strokes (in): 0.5, 1.0, 2.0, 3.0, 4.0, 5.0, 6.0, 7.0, 8.0

Dimensional

Bore Diameter: 0.220 in

Piston Area: 0.038 in²

Supply: Clean, Dry, Unlubricated Air

Pressure Range: Full Vacuum to 125 psi

(0.2 psi differential required for actuation)


Filtration: 5-micron particle filter (coalescing filter recommended)

Mounting

Using Airpot cylinder seals: Stock configurations come with silicone cylinder seals (optional with custom parts). They are an easy and reliable way to mount and seal to each end of the glass cylinder. Make two customer's parts, one for each end of the glass cylinder. These can be designed to have a threaded port, open vent hole or dead ended, depending on the application requirements. Connect two customer's parts together with a baseplate, tie rods, or structural tube.

Customer's Part Pilot Feature: $\varnothing.154 \pm .001 \times .085$ long

Mounting Spacing = Stroke + .525



For more information, see drawing: CYLINDER SEAL TABLE

If using another method to mount the glass, cylinder seals can be removed and discarded.

Piston Friction Coefficient

Approximately 0.2 (static & dynamic)

Piston Leak <0.19 standard Liters /minute at 65 psi

<0.57 standard Liters /minute at 125 psi

Cycle Life

The very long cycle life of this product depends on how the cylinder is used as well as the requirements of your application. Leak will increase slowly as the piston wears with high number of cycles. High loads and especially high side loads along with cycling can increase friction. Typically, cylinders will last from 1 to 25 million cycles before they are replaced.

Environment

Temperature Range:

With standard cylinder seals: -20 °C to +100 °C

With -ET (extreme temperature) cylinder seals: -40 °C to +150 °C

Without cylinder seals: -40 °C to +150 °C



Mass

Cylinder Mass (g) = 1.4 x glass length

Piston Mass (g) = 0.2

Cylinder Seal Mass (g) = 0.06





STOCK
STROKE
LENGTHS

0.5

1.0

2.0

3.0

4.0

5.0

6.0

7.0

8.0

ADDITIONAL OPTIONS

1. Add "-ET" after all other options for
extreme temperature option.

Part Number:

2K S 56 - □ CP

→ STROKE LENGTH

Airpot®

35 LOIS ST
NORWALK CT 06851
US

203-846-2021
www.airpot.com


PART

2K S 56 - CP




REV
0106AF

STOCK 2K56 PISTON/CYLINDER SET

UNITS IN INCHES



3RD ANGLE PROJECTION



1. If using cylinder seals, add "-ET" after all other options for extreme temperature cylinder seals.

Part Description:

2K 56 - ☐ CP ☐

**"J2" FOR CYLINDER SEALS
STROKE LENGTH**

Airpot®

35 LOIS ST
NORWALK CT 06851
US

203-846-2021
www.airpot.com

PART

2K 56 - CP

REV 110623

CUSTOM 2K56 PISTON/CYLINDER SET

UNITS IN INCHES



3RD ANGLE PROJECTION